



## V-BELAY STATION 2 316 DRACO S

**Ref: V53412**

Belay Station Type V in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Two fixing points consisting of two Fixe 1 hangers M10 / M12 screws Anchor point with Draco / Draco with safety screw. Designed and manufactured in Barcelona-Pyrenees. COMPONENT FEATURES Hanger Fixe 1 - Geometry: Rounded inner edge for less wear on the carabiners. Directs the carabiner for an optimal roof work. Conical Washer. Better control of the tightening torque. Three anti-rotation pins. Optimized surface for full contact. Fixe 1 - Hanger features: For bolts M10 / M12. Weight: 57g (10mm) / 56g (12mm). Breaking strength: 25 kN. Material: ecotri zinc plated / 316L stainless steel Ring features: Ring always present between components for a better workability. TIG welding. Better resistance to corrosion. Inside diameter: 33mm. Breaking strength: 25 kN Material: ecotri zinc plated / 316L stainless steel. Features of the 316L stainless steel-chain: TIG welding. Better resistance to corrosion. Reduction of the number of links to three. Less critical points. 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: 316L stainless steel. Features of the ecotri zinc plated-chain: 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: ecotri zinc plated steel. Draco carabiner features: Keylock closing. Oversized friction zone. Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Draco-safety-carabiner features: Keylock closing. Oversized friction zone. Safety screw. Breaking strength: 25kN. Production: 316L stainless steel. Are you sure this is your ideal belay station Find it out: <https://www.fixeclimbing.com/configurator/>

### Información técnica:

Brand:	Fixe
Country of origin:	Spain
Color:	Inox
Material:	316L
Breaking Strenght:	25kN
Configurator:	Si
Diameter:	12mm